



**Baltimore Innovations Ltd**  
Wessex Road, Jacksons Business Park  
Bourne End, Buckinghamshire  
SL8 5DT, United Kingdom  
Tel: +44 (0)1628 531 900  
Fax: +44 (0)1628 531 100  
Email: Sales@BaltimoreInnovations.co.uk

## M-0006-26 ACTIV-STRIP®

### OXYGEN AND MOISTURE ABSORBING LABELS Suitable for Automated Insertion

Moisture Absorbing Film: 0.3mm or 0.6mm thickness

CSP Technologies provides Activ-Strip desiccant film in roll form. The material can be used loose or staked to the heat seal layer of the packaging material.

The roll width can be slit between 10 and 150mm wide as required. The moisture absorbing capacity is given below as capacity per square centimetre area of film. The moisture capacity is linear based on area. The area of film required for your specific application can be determined from this value.

#### TECHNICAL DATA SHEET

Film Thickness	0.6mm	0.3mm
Moisture Capacity	11 mg / cm <sup>2</sup>	5.5 mg / cm <sup>2</sup>
Desiccant	Silica Gel (60% loading by weight)	
Colour	White	
Packaging	Supplied on rolls with 76 mm core Width up to 150 mm Packaged in Foil Bags	
Labelling	Description, Lot Number, other information as requested by customer	
Storage	Room Temperature	

ACTIV-STRIP™ and CSP Technologies logo are trademarks of CSP Technologies, Inc